

CRF450RL



ENGINE

Type: 4-stroke, Unicam® 50HC
Displacement: 449 cc, single-cylinder, 4 titanium valves
Cooling: liquid-cooled

FUEL SYSTEM

Type: programmed fuel injection system (PGM-Fi)
Fuel tank capacity: 7.6 liters

TRANSMISSION

Type: 6-speed manual
Final drive: chain

DIMENSIONS

Overall dimensions (L x W x H): 2192 mm x 846 mm x 1278 mm
Wheelbase: 1496 mm
Seat height: 945 mm
Ground clearance: 320 mm
Weight: 125 kg (ready to ride)

TIRES

Front tire: 120/100-21 IRC GP21
Rear tire: 120/80-18 IRC GP22

BRAKES

Front brake: 260 mm diameter disc with hydraulic double-piston caliper
Rear brake: 240 mm diameter disc with hydraulic caliper

SUSPENSION

Front suspension: inverted Showa® fork, 37 mm diameter, adjustable, 274 mm travel
Rear suspension: Pro-Link® swingarm with adjustable Showa® monoshock, 272 mm travel

INSTRUMENTS & IGNITION

Ignition type: DC CDI

SPECIAL FEATURES

- Titanium fuel tank
- Lithium battery
- Dual radiator
- Skidplate (engine guard)
- Black DID Dirt Star rims
- Factory handguards
- Single exhaust

