

CRF450RX



ENGINE

Type: 4-stroke, Unicam[®] SOHC
Displacement: 449 cc, single-cylinder, 4 titanium valves
Cooling: liquid

FUEL SYSTEM

Type: PGM-FI electronic fuel injection system
Fuel tank capacity: 2.11 gallons (8 liters)

TRANSMISSION

Type: 5-speed manual
Final transmission: chain

DIMENSIONS

Overall dimensions (LxWxH): 85.9 x 32.6 x 49.9 in
(2,182 mm x 828 mm x 1,267 mm)
Wheelbase: 58.3 in (1,481 mm)
Seat height: 38 in (965 mm)
Ground clearance: 13.2 in (335 mm)
Curb weight: 251.3 lb (114 kg)

TIRES

Front tire: 90/90-21 dunlop AT81
Rear tire: 120/90-18 dunlop AT81

IGNITION & INSTRUMENTATION

Ignition type: DC CDI.

BRAKES

Front brake: 10.2 inch (260 mm) hydraulic disc
Rear brake: 9.4 inch (240 mm) hydraulic disc

SUSPENSION

Front suspension: Showa[®] inverted fork, 49 mm diameter, adjustable, 12.2 inch (310 mm) travel
Rear suspension: Pro-Link[®] swingarm with Showa[®] mono-shock, adjustable, 12.3 inch (313 mm) travel

SPECIAL FEATURES

- "HRC launch control" mode, ECU-controlled for more aggressive starts
- 3 selectable power delivery levels
- HSTC torque control
- Nissin hydraulic clutch
- Air filter and airbox improve torque and are easy to clean and maintain
- Resin fuel tank
- Redesigned radiator for improved cooling
- Black DID dirtStar rims
- Skidplate.
- Aluminum renthal fatbar handlebar
- Factory hand guards
- Single exhaust outlet
- Completely redesigned plastics and styling

