

CRF450X



ENGINE

Type: 4-stroke, Unicam[®] SOHC
Displacement: 449 cc, single-cylinder, 4 titanium valves
Cooling: liquid

FUEL SYSTEM

Type: PGM-FI electronic fuel injection system
Fuel tank capacity: 2.01 gallons (7.6 liters)

TRANSMISSION

Type: 6-speed manual
Final transmission: chain

DIMENSIONS

Overall dimensions (L x W x H): 86.3 x 33.3 x 50.3 in
(2,192 mm x 846 mm x 1,278 mm)
Wheelbase: 58.7 in (1,491 mm)
Seat height: 37.9 in (963 mm)
Ground clearance: 13.1 in (333 mm)
Curb weight: 275.6 lb (125 kg)

TIRES

Front tire: 80/100-21 dunlop MX52
Rear tire: 110/100-18 dunlop MX52

BRAKES

Front brake: 10.2 inch (260 mm) hydraulic disc with dual-piston caliper
Rear brake: 9.4 inch (240 mm) hydraulic disc

SUSPENSION

Front suspension: Showa[®] inverted fork, 49 mm diameter, adjustable, 12 inch (305 mm) travel
Rear suspension: Pro-Link[®] swingarm with Showa[®] mono-shock, adjustable, 11.8 inch (300 mm) travel

IGNITION & INSTRUMENTATION

Ignition type: DC CDI
Instrument panel: analog
Main light: 12V / 55W

SPECIAL FEATURES

- Titanium fuel tank
- Lithium battery
- Dual radiator
- Engine skid plate
- Black DID DirtStar rims
- Factory hand guards
- Single exhaust outlet

