

TALON 1000X-4

FOX LIVE VALVE



ENGINE

Type: 4-stroke, UniCam® OHC
Displacement: 999 cc, 2 cylinders, 4 valves
Cooling: liquid-cooled

FUEL SYSTEM

Type: programmed fuel injection (PGM-FI)
Fuel capacity: 6.9 gallons + 0.8-gallon reserve (26.1 liters + 3 liters)

TRANSMISSION

Type: 6-speed dual-clutch transmission (DCT) with reverse and HI/LOW subtransmission
Final drive: direct shaft drive (front and rear)
Drive modes: 2WD and i-4WD
Shift modes: standard, sport, and manual

DIMENSIONS

Overall dimensions (L x W x H): 152.5 x 64 x 78.5 in
(3,874 mm x 1,626 mm x 1,994 mm)
Wheelbase: 116.4 in (2,957 mm)
Seat height: 28 in (711 mm)
Ground clearance: 12.8 in (325 mm)
Curb weight: 1,739 lb (789 kg)

TIRES

Front tires: 28 x 9 - 15
Rear tires: 28 x 11 - 15

BRAKES

Front brake: dual 250 mm hydraulic discs
Rear brake: dual 250 mm hydraulic discs

SUSPENSION

Front: independent double wishbone, 14.6 inch travel (371 mm), with FOX podium 2.5 shocks and live valve electronic adjustment
Rear: 3-link trailing arm, 15.1 inch travel (384 mm), with FOX podium 2.5 shocks and live valve electronic adjustment

IGNITION & INSTRUMENTATION

Ignition type: full transistorized
Instrument panel: digital
Headlight: LED

SPECIAL FEATURE

- Number of seats: 2
- Includes premium alloy wheels
- Only model with automatic transmission and launch control mode
- Roll over protection structure (ROPS)
- Hill-start assist
- "Stadium-style" rear seats for better forward visibility

